

DH-KIT/NVR4104HS-W-S2/4-HFW1120S-W-0360B

4 CH 720P WiFi Network Surveillance Security System



Features

- Easy installation, plug&play
- Support P2P, allowing easier home applications
- Support WPS, make easier connection
- H.264 dual-stream video compression
- HDMI/VGA simultaneous video output
- All channel 720P real-time recording
- Support 2.4GHz and 5GHz dual-bands
- Multiple network monitoring: web-browser, smart phone/tablet app

DH-KIT/NVR4104HS-W-S2/4-HFW1120S-W-0360B

Technical Specifications

Model	DH-KIT/NVR4104HS-W-S2/4-HFW1120S-W-0360B
System	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Video & Audio	
IP Camera Input	4 channel
Two-way Talk	1 channel Input,1 channel Output, RCA
Display	
Interface	1 HDMI, 1 VGA
Resolution	1920 × 1080 , 1280 × 1024, 1280 × 720 ,1024 × 768
Display Split	1/4
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording	
Compression	H.264/MJPEG
Resolution	6Mp/5Mp/4Mp/3Mp/1080P/ 720P/ D1&etc.
Record Rate	80Mbps
Bit Rate	48Kbps ~ 8192Kbps Per Channel
Record Mode	Manual, Schedule (Regular, Continuous), MD(Video detection: Motion Detection, Camera Blank, Video Loss), Alarm, Stop
Record Interval	1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec
Video Detection	
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss and Camera Blank
Playback & Backup	
Sync Playback	1/4
Search Mode	Time/Date, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device/Network/Internal SATA burner
Network	
Ethernet	1RJ-45 port (10/100Mbps)
Wireless Network	Built-in Wifi module, 2 WiFi Antenna
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE,DDNS, FTP, IP Search (Support Dahua IP camera, DVR, NVS, etc.)
Max User Access	128 users
Smart Phone	iPhone, iPad, Android

DH-KIT/NVR4104HS-W-S2/4-HFW1120S-W-0360B

Interoperability	ONVIF 2.4, CGI Conformant	
Storage		
Internal HDD	1 SATA III Port, Up to 6TB capacity for each HDD	
Auxiliary Interface		
USB	2 USB Ports (1 Rear USB2.0, 1 Front USB2.0)	
General		
Power Supply	DC12V/2A	
Power Consumption	NVR: 10W (without HDD)	
Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 0 ~ 90% RH, 86 ~ 106kpa	
Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH	
Camera		
Image Sensor	1/3" 1.3Megapixel progressive scan CMOS	
Effective Pixels	1280(H)x960(V)	
Scanning System	Progressive	
Electronic Shutter Speed	Auto/Manual 1/3(4)~ 1/100000s	
Min. Illumination	0. 1Lux/F2.0(Color), 0Lux/F2.0(IR on)	
S/N Ratio	More than 50dB	
Camera Features		
Max. IR LEDs Length	30m	
IR On/Off Control	Auto/ Manual	
IR LEDs	24	
Day/Night	Auto(ICR)/Color/B/W	
Backlight Compensation	BLC/HLC/DWDR	
White Balance	Auto/Manual	
Gain Control	Auto/Manual	
Noise Reduction	3D	
Privacy Masking	Up to 4 areas	
Lens		
Focal Length	3.6mm	
Max Aperture	F2.5	
Focus Control	Manual	
Angle of View	H:72°, V:53°	
Lens Type	Fixed lens	
Mount Type	Board-in Type	
Video		
Compression	H.264/H.264B/H.264H/MJPEG	
Resolution	1.3MP(1280×960)/720P(1280×720)/ VGA(640×480)/QVGA(320×240)	
Frame Rate	Main Stream	1.3M (1 ~ 25/30fps)s)
	Sub Stream	VGA(1 ~ 25/30fps)
Bit Rate	H264:32K ~ 10Mbps	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Protocol	HTTP;HTTPs;TCP;ARP;RTSP;RTP;UDP;SMTP;FTP;	


DH-KIT/NVR4104HS-W-S2/4-HFW1120S-W-0360B

	DHCP;DNS;DDNS;PPPOE;IPv4/v6;QoS;UPnP;NTP; Bonjour;802.1x;Multicast;ICMP;IGMP;
Wi-Fi	Wi-Fi(IEEE802.11b/g/n),50m(open field)
Compatibility	ONVIF, PSIA, CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android
General	
Power Supply	DC12V
Power Consumption	<3.9W(IR on)
Operating Conditions	-10° C ~ +50° C (14° F ~ +122° F) / Less than 95% RH
Storage Conditions	-10° C ~ +50° C (14° F ~ +122° F) / Less than 95% RH
Ingress Protection	IP67
Carton	
Dimension(W×D×H)	386*238*330mm

PACKAGE:

- NVR4104HS-W-S2 *1
- IPC-HFW1120S-W-0360B *4
- 12V/1A Power Adapter for Camera *4

System Connection



Dahua Technology Co., Ltd.

1199 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuasecurity.com

*Design and specifications are subject to change without notice.

© 2016 Dahua Technology Co., Ltd.