


DHL460UDH-ES

46" FHD Video Wall Display Unit (Ultra Narrow Bezel 1.7mm)



Technical Specification

Model

Model	DHL460UDH-ES
-------	--------------

Display


Diagonal	46" (16:9)
LCD Technology	PVA
Resolution	1920×1080 (FHD)
Bezel width	1.15mm(U/L), 0.55mm(R/B)
Backlight	Direct LED
Brightness/Luminance	700 cd/㎡
Contrast	4000:1
Viewing Angle	H178°, V178°
Response time	8ms
Display Color	8bit(16.7M)
Color Temperature	10,000K
MTBF	50,000h

Signals

Input	CVBS×2, VGA×1, DVI-D×1, HDMI×1, RS232×1, USB×1, Audio in×1, IR×1
Output	CVBS×2, RS232×1, Audio out×1

Features :

- Industrial level PVA LCD panel, suitable for continuous 24/7 operation
- Ultra-narrow 1.7mm bezel-to bezel design(1.15mm bezel on the left and top sides and 0.55mm bezel on the right and bottom sides)
- High contrast and high brightness greatly enhance the video layering, and present the details of the video
- High fidelity digital processing for a brilliant and vivid video
- Built-in 3D COMB filter and 3D noise reduction
- Wide array of connectivity options HDMI, DVI, VGA, BNC, RS232, USB, Audio
- Infrared, RS232 double mode, supporting remote PC control
- Brightness smart detection, power-saving
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Fast stack installation, professional project design, supporting arc-shaped mounting
- Widely used in surveillance center, dispatching platform, safe city, commercial display, etc.



General

Consumption (Standard)	120W	
Consumption (Standby)	≤1W	
Power Supply	AC90~264V (+/-5%), 50/60 Hz	
Installation Mode	Floor-standing, wall-mounted	
Control Signal	Infrared, RS232 double mode, supporting remote PC control	
Net Weight	22.5kg	
Gross Weight	25.5kg	
Dimension	1020.0×574.6×118.7(mm)	
Package(W×H×D)	1210×280×835(mm)	
Work Environment	Temperature	0℃~+50℃
	Humidity	20%~90%

Dimensions(mm)

